

**CEILING REQUIREMENTS**

**DOCUMENT NUMBER: 09500**

**APPLICATION: ELEMENTARY, MIDDLE AND HIGH SCHOOL**

**DATE OF ISSUE: 10/14/2022**

**NOTES:**

Provide lay-in acoustical tile ceiling systems in locations required by the ed spec. Acceptable manufacturers are as follows:

Armstrong: "Ultima 1910 with HumiGuard Plus" Basis of Design 24"x24"

Celotex: [xxx]

U.S.G.: [xxx]

Our acceptance of the above listed systems is contingent upon meeting all code requirements.

Provide hot-dipped galvanized suspended acoustical ceiling grid in locations required by the ed spec. Color shall be white. Acceptable manufacturers are as follows:

Armstrong: "Prelude 15/16", hot dipped"

Celotex: "Celogrid 900 System, hot dipped"

U.S.G.: "DX2 24, galvanized grid"

Chicago Metallic: 211-01H, 1210-01H, 1226-01H, or 1420-01

Provide manufacturers standard minimum ten (10) year warranty against sagging of ceiling panels and rusting of grid. Ceiling tiles shall be humidity resistant such as Armstrong HumiGuard Plus or an approved equal.

Grid spacing shall by 2' x 2'.

In high humidity environments, provide aluminum grid with Humiguard tile.

In food prep areas, provide vinyl-faced tiles, Ceramaguard, or similar,